

INDION[®]

Industrial Downflow Softeners

The INDION Industrial Downflow Softener is a manually operated Ion Exchange unit designed specially for industrial use. It is simple to operate, inexpensive to maintain and is widely used in the industry.

The softener comprises a steel pressure vessel containing a bed of cation exchange resin, a regenerating system and control valves.

A strongly acidic cation exchange resin in sodium form is used to exchange sodium ions for the hardness-forming calcium and magnesium ions, and thus produce soft water. At the end of each service cycle, the ion exchange resin is regenerated with sodium chloride solution, after which the unit is ready for the next service cycle.

For larger plants, a brine measuring tank is provided, and a separate salt saturator, preferably in concrete, is recommended for bulk storage of salt and preparation of brine. Standard equipment is available to soften water, upto a maximum flow rate of 275 m³/h.

Advantages

- Easy to install and operate.
- Produces clear, soft and non-scale forming water.
- Low operating costs.
- Incorporates INDION high-capacity polystyrene bead type cation exchange resin which is remarkably stable and has long life.

Specifications

- One mild steel pressure vessel provided with an inlet distributor, an outlet collecting system and a brine distributor. The vessel is painted externally with a protective coat of red oxide and internally with anti-corrosive bituminous paints.
- One set of control valves, with all piping to inlet and outlet terminals.



- One combined salt/brine measuring tank, provided with brine suction piping with adjustable indicating clamp, hydraulic ejector and control valve.
- One orifice board for indicating wash and resin flow rates (to be fitted in the drain sump).
- One charge of INDION cation exchange resin with supporting underbed.
- One hardness test kit for testing the softened water.

Optional

One set of fittings for concrete salt saturator, wherever applicable, to be constructed by the client.

Technical Data

Model	Max Flow Rates	Working Pressure		Regenerants	
		Min	Max	Sodium Chloride 100%	
		Kg/cm ² g	Kg/cm ² g	Min.	Max.
	M ³ /h			Kg	Kg
S 6015/D	13.0	2.0	3.5	29.0	58.0
S 6025/D	13.0	2.0	3.5	29.0	58.0
S 8015/D	23.0	2.0	3.5	51.0	102.0
S 8025/D	23.0	2.0	3.5	51.0	102.0
S10015/D	35.0	2.0	3.5	80.0	161.0
S10025/D	35.0	2.0	3.5	80.0	161.0
S12020/D	50.0	2.0	3.5	116.0	170.0
S12025/D	50.0	2.0	3.5	116.0	231.0
S14020/D	70.0	2.0	3.5	157.0	231.0
S14025/D	70.0	2.0	3.5	157.0	313.0
S16020/D	90.0	2.0	3.5	204.0	299.0
S16025/D	90.0	2.0	3.5	204.0	408.0
S18020/D	114.0	2.0	3.5	259.0	381.0
S18025/D	114.0	2.0	3.5	259.0	517.0
S20020/D	140.0	2.0	3.5	327.0	476.0
S20025/D	140.0	2.0	3.5	327.0	639.0
S22020/D	170.0	2.0	3.5	388.0	578.0
S22025/D	170.0	2.0	3.5	388.0	775.0
S24020/D	200.0	2.0	3.5	459.0	692.0
S24025/D	200.0	2.0	3.5	459.0	926.0
S26020/D	240.0	2.0	3.5	541.0	808.0
S26025/D	240.0	2.0	3.5	541.0	1081.0
S28020/D	275.0	2.0	3.5	628.0	937.0
S28025/D	275.0	2.0	3.5	628.0	1255.0
S30020/D	275.0	2.0	3.5	724.0	1081.0
S30025/D	275.0	2.0	3.5	724.0	1448.0

Note : 1. Feed water should be free from turbidity, organic matter, heavy metals, free chlorine and oil and design parameters based on 25°C
2. Output between regenerations will vary with influent feed water quality.

To the best of our knowledge the information contained in this publication is accurate. Ion Exchange (India) Ltd. maintains a policy of continuous development and reserves the right to amend the information given herein without notice. Please contact our regional offices for current product specifications.

IONINDIA is the registered trademark of Ion Exchange (India) Ltd.



CORPORATE OFFICE

Tiecicon House, Dr. E. Moses Road, Mahalaxmi, Mumbai 400 011.
Tel: 022-2493 9520/23/25 Fax: 022-2493 8737
E-mail: ieil@ionexchange.co.in; hocro@ionexchange.co.in

REGIONAL OFFICES

CHENNAI

Tel: 044-2815 3293, 2815 0807 Fax: 044-2815 3361
E-mail: chcro@ionexchange.co.in

DELHI

Tel: 011-2577 1160/6061, 2577 1348 Fax: 011-2577 4837
E-mail: delcro@ionexchange.co.in

KOLKATA

Tel: 033-2400 4341/49, 2400 0797 Fax: 033-2400 4345
E-mail: calcro@ionexchange.co.in

MUMBAI

Tel: 022-2493 9520/23/25 Fax: 022-2493 8737
E-mail: hocro@ionexchange.co.in

VADODARA

Tel: 0265-239 6506, 239 7638 Fax: 0265-239 8508
E-mail: brdcro@ionexchange.co.in

BRANCH OFFICES

- Bangalore - Tel: 080-528 4696/7, 526 3904 Fax: 080-529 5795
E-mail: bngcro@ionexchange.co.in
- Chandigarh - Tel: 0172-745 011 Fax: 0172-744 594
E-mail: chd.general@ionexchange.co.in
- Hyderabad - Tel: 040-2339 7760 Fax: 040-2339 7761
E-mail: hydrcro@ionexchange.co.in
- Indore - Tel: 0713-506 4875 Fax: 0731-504 1578
E-mail: indore.gen@ionexchange.co.in
- Lucknow - Tel: 0522-223 8589 Fax: 0522-223 8545
E-mail: luk.general@ionexchange.co.in
- Pune - Tel: 020-714 6063 Fax: 020-714 6109
Email: pun.general@ionexchange.co.in

FACTORIES

•Ankleshwar •Hosur •Patancheru •Rabale •Verna

ALL INDIA NETWORK OF SERVICE COMPANIES AND DEALERS